

## しんごうげん

信 号 用 ケ ー

種類 (呼び名)	線心構成	線心数	線				心		mm 絶縁紙厚	mm ゴム引綿テープ厚		シース mm		
			導体		mm ビニール 絶縁体厚	mm 紙絶縁体 厚	mm ゴム絶縁 体厚	線心	シース		ビニール		ゴム	
			mm <sup>2</sup> 公称断面積	外径 mm							ビニール	ゴム	鉛被	
信号鉛被油紙	19/1.4	2	30	7.0		2.0		1.5						1.3
	19/0.8	2	10	4.0	"	"	"	"						"
	"	4	"	"	"	"	"	"						"
	7/0.8	2	3.5	2.4										"
	"	4	"	"	"	"	"	"						"
	"	7	"	"	"	"	"	"						"
	"	12	"	"	"	"	"	"						1.4
	"	19	"	"	"	"	"	"						1.5
	"	30	"	"	"	"	"	"						1.7
	1.6	2	2.0	1.6										1.3
	"	4	"	"	"	"	"	"						"
	"	7	"	"	"	"	"	"						"
信号鉛被油紙 がい装油紙	19/1.4	2	30	7.0		"		"						1.3
	19/0.8	2	10	4.0	"	"	"	"						"
	"	4	"	"	"	"	"	"						"
	7/0.8	2	3.5	2.4										"
	"	4	"	"	"	"	"	"						"
	"	7	"	"	"	"	"	"						"
	"	12	"	"	"	"	"	"						1.4
	"	19	"	"	"	"	"	"						1.5
	"	30	"	"	"	"	"	"						1.7
	1.6	2	2.0	1.6										1.3
	"	4	"	"	"	"	"	"						"
	"	7	"	"	"	"	"	"						"
信号キヤブタイヤ (通称ゴム)	19/0.8	2	10	4.0				1.4	0.1	0.25	0.5			2.3
	"	4	"	"				"	"	"	"			2.5
	7/0.8	2	3.5	2.4			1.1	"	"	"	"			1.8
	"	4	"	"			"	"	"	"	"			2.0
	"	7	"	"			"	"	"	"	"			2.3
	"	12	"	"			"	"	"	"	"			2.9
	"	19	"	"			"	"	"	"	"			3.3
	"	30	"	"			"	"	"	"	"			4.1
	7/0.6	2	2.0	1.8			"	"	"	"	"			1.7
	"	4	"	"			"	"	"	"	"			1.8
	"	7	"	"			"	"	"	"	"			2.1
	"	12	"	"			"	"	"	"	"			2.6
信号二ル	"	19	"	"			"	"	"	"	"			3.0
	"	30	"	"			"	"	"	"	"			3.7
	1.6	2	"	1.6			"	"	"	"	"			1.6
	"	4	"	"			"	"	"	"	"			1.8
	"	7	"	"			"	"	"	"	"			2.1
	"	12	"	"			"	"	"	"	"			2.5
	"	19	"	"			"	"	"	"	"			2.9
	"	30	"	"			"	"	"	"	"			3.6
	7/0.6	2	2.0	1.8			"	"	"	"	"			1.7
	"	4	"	"			"	"	"	"	"			1.8
	"	7	"	"			"	"	"	"	"			2.1
	"	12	"	"			"	"	"	"	"			2.6
信号二ル	"	19	"	"			"	"	"	"	"			3.0
	"	30	"	"			"	"	"	"	"			2.3
	1.6	2	"	1.6			"	"	"	"	"			1.7
	"	4	"	"			"	"	"	"	"			"
	"	7	"	"			"	"	"	"	"			"
	"	12	"	"			"	"	"	"	"			"
	"	19	"	"			"	"	"	"	"			1.9
	"	30	"	"			"	"	"	"	"			2.3
	"	61	"	"			"	"	"	"	"			3.0